

PREMIUM FLOOR SAWS



SOLUTIONS THAT LAST



FS1C-14 AND FS1C-18 PREMIUM FLOOR SAWS

Why buy a Premium Floor Saw?

Far more money is spent on diamond blades consumed over the useful life of a floor saw, than on the saw itself. That said, it simply makes sense to purchase a premium saw in order to improve blade performance and life. A premium saw provides the highest return on total dollars spent for sawing applications.



The FS1C is a heavy saw at up to 245 and 290 lbs. without fuel or water.

Moreover, the FS1C's center of gravity is low and weight distribution arranged to eliminate flex and vibration during operation. In similar fashion, the FS1C features a heavy duty blade shaft and bearing assembly as well as balanced engine and blade shaft pulleys. These design considerations go to providing operating conditions most favorable to optimal blade performance and life. The smoother and truer blades run, the longer they last.

Other Premium Features include:

- Heavy duty front and rear axles with over-sized tire assemblies, all housed within the body of the saw for low maintenance and accurate tracking
- Easy to use cutting depth gauge, calibrated for blade size
- Heavy duty, two piece, hinged, spring tensioned blade guard for positive up or down positioning and minimal vibration
- Blade guard mounts to either side of the saw for right or left side cutting
- Adjustable guiding handle
- 2 and 3 v-belt drive systems for GX240 and GX390 saws, respectively
- Fluted, removable water manifolds that resist clogging while delivering up to 5 gallons of fluid/minute
- Interchangeable water tank and hose hook ups
- Wrench and shaft key housed on saw for immediate access
- Optional water tank conversion kit

SPECIFICATIONS	FS1C-14H	FS1C-14T	FS1C-18H	FS1C-18T
L x W x H (Handle Down, Pointer Up)	41 x 25 x 35 in (104 x 64 x 89 cm)	41 x 25 x 44 in (104 x 64 x 112 cm)	41 x 25 x 35 in (104 x 64 x 89 cm)	36 x 25 x 44 in (104 x 64 x 112 cm)
Operating Weight	245 lb (111 kg)	Full Fuel, Full Water 325 lb (147 kg)	290 lb (132 kg)	Full Fuel, Full Water 370 lb (168 kg)
Water Tank Capacity		10 gal (38 liter)		10 gal (38 liter)
Max. Blade Diameter	14" (35.5 cm)		18" (45.7 cm)	
Max. Cut Depth	4.63 in (11.75 cm)		6.63 in (16.83 cm)	
Engine	Honda GX240		Honda GX390	

() Metric Measurements.
Specifications subject to change without notice.



MBW Inc.
250 Hartford Road • P.O. Box 440
Slinger, Wisconsin • 53086-0440 • USA
Ph: 800-678-5237 or 262-644-5234 • Fax: 262-644-5169
E-mail: mbw@mbw.com • Website: www.mbw.com

MBW UK Ltd.
Units 2 & 3 Cochrane Street • Bolton BL3 6BN • England UK
Ph: 44 (0) 1204 387784 • Fax: 44 (0) 1204 387797
E-mail: mbwuk@btinternet.com • Website: www.mbw.com

MBW FRANCE S.A.R.L.
Z.A. d'Outreville • 5 rue Jean Baptiste Néron • 60540 BORNEL • France
Ph: 33 (0) 3 44 07 15 96 • Fax: 33 (0) 3 44 07 41 28
E-mail: mbwfrance@free.fr • Website: www.mbw.com

AUTHORIZED DISTRIBUTOR